



US006167037A

United States Patent [19]

Higuchi et al.

[11] Patent Number: 6,167,037

[45] Date of Patent: Dec. 26, 2000

[54] SIGNAL TRANSMITTING METHOD, TRANSMITTER, RECEIVER, AND SPREAD-SPECTRUM CODE SYNCHRONIZING METHOD FOR MOBILE COMMUNICATION SYSTEM

[75] Inventors: Kenichi Higuchi, Yokosuka; Mamoru Sawahashi, Yokohama; Fumiya Adachi, Yokohama; Koji Ohno, Yokohama; Akihiro Higashi, Yokosuka, all of Japan

[73] Assignee: NTT Mobile Communications Networks Inc., Tokyo, Japan

[21] Appl. No.: 08/952,081

[22] PCT Filed: Mar. 4, 1997

[86] PCT No.: PCT/JP97/00657

§ 371 Date: Nov. 3, 1997

§ 102(c) Date: Nov. 3, 1997

[87] PCT Pub. No.: WO97/33400

PCT Pub. Date: Sep. 12, 1997

[30] Foreign Application Priority Data

| | | | |
|---------------|------|-------|----------|
| Mar. 5, 1996 | [JP] | Japan | 8-047774 |
| Jun. 24, 1996 | [JP] | Japan | 8-163462 |
| Oct. 15, 1996 | [JP] | Japan | 8-272696 |

[51] Int. Cl.⁷ H04B 7/216

[52] U.S. Cl. 370/335; 370/342; 370/441; 370/503

[58] Field of Search 370/335, 342, 370/441, 320, 350, 515, 503, 509, 519; 375/200, 208, 209, 210, 359, 365, 367

[56] References Cited

U.S. PATENT DOCUMENTS

| | | | |
|-----------|--------|-----------------|---------|
| 5,111,478 | 5/1992 | McDonald | 375/200 |
| 5,329,547 | 7/1994 | Ling | 370/342 |
| 5,345,469 | 9/1994 | Fulghum | 370/342 |
| 5,535,239 | 7/1996 | Padovani et al. | 370/209 |
| 5,790,588 | 8/1998 | Fukawa et al. | 375/200 |

FOREIGN PATENT DOCUMENTS

| | | |
|----------|--------|-------|
| 5-506763 | 9/1993 | Japan |
| 6-501349 | 2/1994 | Japan |

Primary Examiner—Hassan Kizou

Assistant Examiner—Mitchell Slavitt

Attorney, Agent, or Firm—Brown Raysman Millstein Felder Steiner LLP

[57] ABSTRACT

Achieving high speed spreading code synchronization of a forward link control channel. A control channel information signal and traffic channel information signals are each spread by different first spreading codes which are fed from a first spreading code (short code) generator (11), and which have a period equal to the period of an information symbol. Subsequently, only the control channel information signal is spread by a third spreading code which is fed from a third spreading code (long code masked portion complex conjugate code) generator (12), and which has a form of complex conjugate of a long code (second spreading code) used for spreading in common. The signals of the entire channels are summed up by an adder (13) at appropriate timings, and the resultant sum is spread by the second spreading code fed from a second spreading code generator (14), thereby being output as a spread modulation signal.

30 Claims, 31 Drawing Sheets

